ESG

EC Declaration of Performance

Product Type:	Clear Float Heat Strengthened		
Product Code:	ESG Clear Heat Strengthened 12mm		
	Basic soda lime silicate glass intended to		
Intended Use:	be used in buildings and construction		
	works.		
Manufacturer:	ESG Group Ltd, 1 Freebournes Road, Witham, Essex, CM8 3UN		
Year marking was affixed:	2012		
System of Attestation of Conformity:	System 4		
Applicable Standard:	EN 1863-2		
Third Party Approval Licence No:	KM511207		
Certification Body & Identification No.	BSI		0086
Person Empowered to Sign the DOP on behalf of the			Stephen Johnston
Manufacturer & Position Held:			Group QHSE
	AAPIL		Manager
Location & date:	Witham		01/05/2021
Characteristics	1		
Resistance to fire:		NPD	
Reaction to fire:		*A1	
External fire performance:		NPD	
Bullet resistance:		NPD	
Explosion resistance:		NPD	
Burglar resistance:		NPD	
Pendulum body impact resistance:		NPD	
Resistance against sudden temperature changes and temperature differentials:	К	*100	
Wind, snow, permanent and imposed load resistance:	mm	*12	
Direct airborne sound insulation:	dB	*36	
Thermal properties:			
- Normal emissivity of coated glass surface:	W/(m² K)	*0.89	
- Thermal transmittance (U-value):		NPD	
Radiation properties:			
- Light transmission:		*0.87	
- Light reflection:		*0.08	
- Solar energy transmission:		*0.72	
- Solar energy reflection:		*0.07	

NPD = No Performance Determined

It is the responsibility of the users of this information to ensure that the intended application of glass products is appropriate and complies with all relevant laws, regulations, standards, codes of practices and other requirements.

^{*=}Performance obtained through glass suppliers EC declaration of performance data.