

## **EC Declaration of Performance**

| Clear Float Heat Strengthened   |                         |   |
|---|-------------------------|---|
| ESG Clear Heat Strengthened 6mm   |                         |   |
| Basic soda lime silicate glass intended to be used in buildings and construction works. |                         |   |
| ESG Group Ltd, 1 Freebournes Road,<br>Witham, Essex, CM8 3UN                            |                         |   |
| 2012  |                         |   |
| System 4  |                         |   |
| EN 1863-2   |                         |   |
| KM5112  |                         | .207                                      |
| BSI   |                         | 0086                                      |
| 4   |                         | Stephen Johnston<br>Group QHSE<br>Manager |
| Witha   | am                      | 01/05/2021                                |
|   |                         |   |
|   | NPD                     |   |
|   | *A1                     |   |
|   | NPD                     |   |
| K   | *100                    |   |
| mm  | *6                      | 1   |
| dB  | *32                     |   |
| /(m² K)   | *0.89<br>NPD            |   |
|   | *0.91<br>*0.08<br>*0.89 |   |
|   |                         | *0.08                                     |

NPD = No Performance Determined

It is the responsibility of the users of this information to ensure that the intended application of glass products is appropriate and complies with all relevant laws, regulations, standards, codes of practices and other requirements.

<sup>\*=</sup>Performance obtained through glass suppliers EC declaration of performance data.